



Sticker Price : \$31,450.00

Discount : 14.00 % OFF

Discounted Price : \$27,047.00

- Machine Assets**
- Kubota D1703 engine
 - 580mm bucket with teeth
 - Swing boom
 - A/C
 - Rubber Truck
 - H/L speed
 - Auxiliary hydraulic Pipeline
 - Heated cab
 - Two year warranty

- Extended Warranty**
- 3 years or 3000 hours(+\$811.00)
 - 4 years or 4000 hours(+\$1,352.00)
 - 5 years or 5000 hours(+\$2,434.00)

- Factory Options**
- Hydraulic Thumb(+\$825.00)
 - Quick Hitch Aux Pipeline(+\$375.00)
 - Second Aux. Pipeline(+\$1,500.00)
 - Tilt Blade(+\$2,600.00)

- Machinery Accessories**
- Mechanical quick hitch (+\$460.00)
 - Hydraulic Quick Hitch (+\$900.00)
 - 350 mm bucket with teeth (+\$484.00)
 - 800 mm Hydraulic Tilt Bucket (+\$792.00)
 - 1000 mm Tilt Bucket (+\$1,100.00)

Machine Specification

Machinery Size		Tech. Specifications		Working Range	
(mm) Total Length	4919	(l³/mm) Standard Bucket Capacity/Length	0.2/580	(mm) Max. Digging Height	4800
(mm) Total Width	1755	(rmp) Swing Speed	1-11	(mm) Max. Dumping Height	3406
(kg) Machine Weight (with all fluids)	3800	(°) Gradeability	30	(mm) Max. Digging Depth	3208
(mm) Cabin Height	2525	(KN) Max. Bucket Digging Force	30	(mm) Max. Vertical Digging Depth	2957
(mm) Axle Base	1670	(KN) Max. Arm Digging Force	18	(mm) Max. Digging Radius	5480
(mm) Wheel (track) Distance	1420	Engine Model	KUBOTA D1703	(mm) Max. Swing Radius	2530
(mm) Minimum Ground Clearance	295	(Kw(HP)/rpm) Power/Revolution speed	18.2[24.4]/2200	(mm) Max. Dozer Blade Lifting Distance	365
(mm) Tail Swing Radius	870	(MPa) System Pressure	27	(mm) Max. Dozer Blade Cutting Distance	385
		(L) Fuel Tank Capacity	42		
		(L) Hydraulic Circuit Capacity	30		
		(L) Cooling Circuit Capacity	9		
		(L) Engine Oil Capacity	8		
		(m³) Bucket capacity	0.12		
		Load Sensing System	YES		
		Pump - Variable-output Piston Pump - axial	YES		
		Manufacturer Hydraulic Pump	Hengly		
		Manufacturer Travel Hydraulic Motor	LKC Hydraulics		
		Manufacturer Swing Hydraulic Motor	RunSun Hydraulic		

